

23 GHz (21.2 - 23.6) High-Performance Microwave Antennas

FEATURES

- Antenna diameters
 - 1' (30 cm)
 - 1.5' (45 cm)
 - 2' (60 cm)
 - 3' (90 cm)
 - 4' (120 cm)
- Antenna weights
 - 1' 17 lbs. (7.7 kg)
 - 1.5' 19 lbs. (8.6 kg)
 - 2' 27 lbs. (12.2 kg)
 - 3' 50 lbs. (22.5 kg)
 - 4' 85 lbs. (38.3 kg)
- **HP models**: high-performance, plane polarized
- **HPD models**: dual polarized
- IEC or EIA flanges available
- **Direct mounting** for RF units available
- Ease of installation: antennas shipped completely assembled, minimal mount required
- Planar radomes standard with high-performance model
- **Rugged and lightweight** cast aluminum mount with fine adjustment for both azimuth and elevation
- Compact size, due to Radio Waves innovative feed design
- Standard white; other colors and/or logos available on request
- Corrosive resistant: coated aluminum, hot dipped galvanized steel and stainless steel
- Three year warranty



21.2 - 23.6 GHz ELECTRICAL SPECIFICATIONS (typical performance)*

Model Number	Diameter ft (cm)	G Low	ain, dBi Mid	High	Beamwidth Degrees, 3dB	X Pol. Disc., dB	F/B Ratio, dB	VSWR Max (R.L., dB)
				Plaı	ne Polarized			
HPLP1-23	1 (30)	34.7	35.1	35.5	2.7	30	62	1.4:1 (15.5)
HPLP1.5-23	1.5 (45)	36.8	37.2	37.8	2.1	30	64	1.4:1 (15.5)
HP2-23	2 (60)	39.7	40.2	40.7	1.7	30	68	1.4:1 (15.5)
HP3-23	3 (90)	43.2	43.7	44.2	1.1	30	71	1.4:1 (15.5)
HP4-23	4 (120)	45.7	46.2	46.6	0.8	30	72	1.4:1 (15.5)
				Dua	al Polarized			
HPLPD1-23	1 (30)	34.5	34.9	35.3	2.7	30	62	1.4:1 (15.5)
HPLPD1.5-23	1.5 (45)	36.6	37.0	37.6	2.1	30	64	1.4:1 (15.5)
HPD2-23	2 (60)	39.5	40.0	40.5	1.7	30	68	1.4:1 (15.5)
HPD3-23	3 (90)	43.0	43.5	44.0	1.1	30	71	1.4:1 (15.5)
HPD4-23	4 (120)	45.5	46.0	46.4	0.8	30	72	1.4:1 (15.5)

^{*} All specifications subject to change without notice.

For regulatory compliances, contact Radio Waves.